

DCT6/DCT2/DCTXP2/DCT10

Wireless Door Contacts



DCT6

NEW 2018!

DCT2

DCTXP2

DCT10

Description

Paradox offers a wide variety of door contacts to provide solutions for different applications, including on-frame and in-frame installation solutions.

All our door contacts provide rock solid stability with Paradox wireless networks as well as long life with cost effective powerful alkaline/lithium batteries.

The DCT2, DCTXP2 and DCT10 are designed to be installed on the frame of doors and windows and differ by range and size. The DCT6 is designed for discrete in-frame door installations with press fit or screw fit with flange.

Using powerful, small-sized magnet gap between the contact and magnet it is secured to operate for at least 10 mm (0.4 in.).

The DCT2, DCTXP2 and DCT10 are offered in 433 or 868 MHz models, while the DCT6 is offered with built-in selectable 433 MHz/868 MHz frequency.

Selection

All Paradox door contacts include an anti-tamper switch while the DCT10 includes cover and wall tamper detection passing EN50131 Grade 2. All the contacts are fully supervised including their battery level.

Beautifully designed, solid stability and wide range for different requirements, Paradox wireless door contacts provide a true solution for installation needs.

Features

- ▶ 433 or 868 MHz models, selectable on DCT6
- ▶ Durable long life cost effective alkaline/lithium batteries
- ▶ Indoor range of 40 to 70 m (130 to 230 ft)
- ▶ Anti-Tamper switch (Dual wall/cover on DCT10)
- ▶ 2 zone capability with zone input (DCTXP2, DCT10)
- ▶ Powerful magnet guaranteed to operate at 10 mm (0.4 in.)
- ▶ Supervised and battery level monitored



Technical Specifications

| | DCT6 | DCT2 | DCTXP2 | DCT10 |
|---|---|---|--|--|
| Power | 1 x AAA alkaline battery | 1 x 3V lithium battery (DL2450) | 2 x AAA alkaline batteries | 3 x AAA alkaline batteries |
| RF Frequency | Selectable 433 or 868 MHz on-board | 433 or 868 MHz models | | |
| Battery Life | 3 years* | | | 4 years* |
| Wireless Range** MG5000/MG5050/RTX3 | 40m (130 ft) | | | 70m (230 ft) |
| Wireless Range** MG6250 | 20m (65 ft) | | | 30m (100 ft) |
| Operating Temperature | -20°C to 50°C (-4°F to 122°F) | | | |
| Dimensions | 7.3 x 2.1 x 2.1 cm (2.8 x 0.8 x 0.8 in.) | 4.3 x 3 x 1.8 cm (1.7 x 1.2 x 0.7 in.) | 11 x 3.2 x 2.5 cm (4.4 x 1.3 x 1.0 in.) | 12.5 x 4.6 x 2.5 cm (4.9 x 1.8 x 1.0 in.) |
| Anti-Tamper Switch | Cover Opening | | | Dual (Cover, wall) |
| 2 Zones (Zone Input) | - | - | ✓ | ✓ |
| Approvals | CE, EN50131 Grade 2 | CE | | CE, EN50131 Grade 2 |
| Remarks | In-frame Installation | Door/window | Door/window | High traffic |
| Supervision | Live supervision, battery low | | | |

*Based on 10 openings/closings a day

**Wireless range is based on typical indoor installation

Compatible Products


Paradox wireless door contacts are compatible with the following products:



MG6250
2-Partition 64-Zone
Wireless Console with
GPRS/GSM




MG5000
32-Zone Wireless
Transceiver Control
Panel



MG5050
32-Zone Wireless
Transceiver Control
Panel



RTX3
Wireless Expansion
Module



RX1
Wireless Receiver



K641LX
32-Character Blue LCD
Keypad with Built-in
Transceiver



K32LX
32-Character Hardwired
LCD Keypad with Built-in
Transceiver